


basic wire and cable

3900 N. ROCKWELL ST. CHICAGO, ILLINOIS 60618-3730, TEL: (773) 539-1800, FAX: (773) 539-3500

BARE COPPER

Stranded
Soft-Medium-Hard Drawn



Stranded Bare Copper

APPLICATIONS:

Stranded (medium or hard-drawn temper) for use overhead outdoors on insulators for distribution circuits.
Stranded (hard, medium or soft-drawn temper) for grounding.

CONSTRUCTION:

Soft or annealed, bare concentric stranded copper conductor.

STANDARDS:

1. Conforms to ASTM B-3 "Soft or Annealed Copper Wire."
2. Conforms to ASTM B-8 for "Concentric-Lay Stranded Copper Conductors."

BASIC CAT NO.	SIZE/ AWG. KCMIL	NO. OF STRDS.	O.D. in.	WEIGHT lbs/mft
4-205	14	7	.073	13
4-206	12	7	.092	20
4-208	10	7	.116	32
4-210	8	7	.146	51
4-212	6	7	.184	81
4-214	4	7	.232	129
4-216	2	7	.292	205
4-217	1	19	.332	259
4-218	1/0	19	.373	326
4-219	2/0	19	.419	411
4-220	3/0	19	.470	518
4-221	4/0	19	.528	653
4-225	250	37	.575	772
4-226	300	37	.630	926
4-227	350	37	.681	1081
4-229	500	37	.813	1544
4-231	750	61	.998	2316
4-232	1000	61	1.15	3088
4-233	1250	91	1.29	3859
4-234	1500	91	1.41	4631
4-235	1750	127	1.53	5403
4-236	2000	127	1.63	6175

Dimensional data not binding. We reserve the right to alter specifications without notice.
SHIPPING TOLERANCE +/- 10%



BWC-4-200

